BK1MAR





Contatto magnetico wireless per porte e finestre;Portata radio in aria libera 100 mt.;Completo di magnete; Antimanomissione e antistrappo;Frequenza di lavoro 868 Mhz protocollo proprietario KODINIS (EXT116S) ;Colore marrone;Alimentato con batteria al litio da 3.6V.

SCHEDA TECNICA

Tipologia	Contatto magnetico wireless
Frequenza di trasmissione	868.0 MHz
Portata di trasmissione	100 m. in aria libera
Copertura	---
Portata di Rivelazione	---
Protezione	Antimanomissione e Antistrappo
Funzioni	---
Batteria	ER14250 (Litio 3,6V) 0,75A
Dimensioni	75 x 27 x 23,6 mm.
Colore Contenitore	Marrone
Certificazioni	EN50131-1; ROHS
Compatibilità	EXT116S, P16, P32, P64
Description	Magnetic door contact
Compatible receivers	P series panels, EXT116s
Operating frequency	868 MHz
Communication range in bu	Up to 100m
Communication with hoppin	Selectable
2-way technology	Yes
Contact Open transmission	Yes
Contact Close transmissio	Yes
Tamper Changed transmissi	Yes
Battery low status transm	Yes
Supervision transmission	Every 1 hour
In-built magnetic contact	Yes
In-built inputs for exter	-
External detector = magne	-
External detector = rolle	-
External detector = vibra	-
Unique ID number for magn	Yes
Unique ID number for ever	-
Power supply	Lithium battery, ½ AA, 3.6V
Color	Brown
Overall dimensions W x H	27 x 23.6 x 75
Operating humidity	0% - 70%
Operating temperature	-5°C up to +50°C